



POLO-BIOPHILIC

POLO-BIO is a suspended biophilic luminaire, which blends the profound connection we have with the natural world with architectural lighting, but has a substantial lumen package to go with it.

Available in 500mm, 700mm 900mm diameters as standard, with direct or direct/ indirect distribution, in a range of outputs to suit your needs.

- Efficacy of up to 111 lm/W
- Colour temperatures: 3000°k and 4000°k
- Colour Finishes: White (9016), Black (9005) or Silver (9006). Other RAL colours available on request
- Dimming options: DALI 1-100% Dim, DSI, Switch Dim, 1-10v
- Wireless control options: Casambi
- Biophilic Option: Hanging faux Plants or Acoustic Moss
- Luminaire supplied complete with individual wire suspensions, which are adjustable up to 3m length as standard*
- Custom length wire suspension, Clear, Black or White flex are also available
- Special Outputs available upon request
- Emergency options: Standard 3hr, Self-Test, Dali addressable or 3hr Dali Wireless Sentinel

Technical

Product	POLO-BIO
Mounting type	Suspended
Standard Diameter	500-900mm
Lumens	3109-11196 Llm
Efficacy	Upto 111 lm/W
Colour Temperature	Warm White (3K) Neutral White (4K)
Optics	Opal diffuser
Control	DALI 1-100%, DSI, 1 -10V, Casambi
Emergency	3 hour, DALI, Self-Test, 3 hour DALI Wireless Sentinel
Biophilic	Hanging faux plants Acoustic Moss
Rendering	Ra80+
IP Rating	IP20
Safety Class	Class 1
MacAdam	SDCM 3
L70/B10	>50K