



TL200

TL200 is an architectural slimline cylindrical downlight. Constructed with extruded aluminium housing with cast aluminium heat sink and aluminium reflector. Suspended version can be mounted at various heights, to create an architectural feature.

- Efficacy of up to 148 lm/W
- Colour temperatures: 3000°k or 4000°k as standard
- Colour Finishes: White (9016), Black (9005), Other RAL colours, available on request.
- Available in 10°, 30° or 45° beam angles to suit your application
- Dimming options: DALI 1-100% Dim, DSI, Switch Dim
- Wireless control options: Casambi
- Snoot options: Black snoot as standard, White available on request
- Emergency options: Standard 3hr, Self-Test, Dali addressable or 3hr Dali Wireless Sentinel

Technical

Product	TL200
Mounting type	Surface Suspended
Diameter	200mm
Lumens	2433 - 3244lm
Efficacy	Up to 148 lm/W
Colour Temperature	Warm White (3K) Neutral White (4K)
	10°
Beam Angles	30° 45°
Dimming	DALI 1-100%, DSI, Switch Dim, Casambi
Emergency	3 hour, DALI, Self-Test, DALI Wireless Sentinel
Rendering	Ra80
IP Rating	IP20
Safety Class	Class 1
MacAdam	SDCM 3
L70/B10	>50K


TL200

Luminaire Order Builder

TL200

STEP 1. Select Mounting	STEP 2. Current	STEP 3. Optics	STEP 4. CCT	STEP 5. Control	STEP 6. Finish	STEP 7. Emergency
SF Surface FS Flex suspended	45 450mA 2433Lm - 16.4W 50 500mA 2704Lm - 18.2W 55 550mA 2974Lm - 20W 60 600mA 3244Lm - 21.8W	10 10° degree beam 30 30° degree beam 45 45° degree beam	3K 3000K 4K 4000K	FO Fixed Output A1 DALI 1-100% Dim A2 DSI A3 Switch Dim A5 Casambi	W RAL9016M B RAL9005 Z CUSTOM	E3 Standard 3 Hour ED DALI/EMPRO ES Self-Test EW 3 hour DALI Wireless Sentinel

All electrical and optical data subject to $\pm 10\%$ tolerances.
Values based on 4000K Colour temperature and CRI80.
CRI90 available upon request.



Dimensions

D Ø	H	Finish		
RAL	Code	Colour Swatch		
200	220	White	9016M	
		Black	9005	
		Custom*	Custom*	

All dimensions are measured in millimetres (mm)

*Custom Colours upon request

TL200

TL200-FS Ancillaries

Clear 0.75mm², Supply Cable		Ancillaries images	
3 core, Clear, 3m	FL-3C-C-3M		
3 core, Clear, Custom Length*	FL-3C-C-ZM		
5 core, Clear, 3m	FL-5C-C-3M		
5 core, Clear, Custom Length*	FL-5C-C-ZM		
6 core, Clear, 3m	FL-6C-C-3M		
6 core, Clear, Custom Length*	FL-6C-C-ZM		
Black 0.75mm², Supply Cable			
3 core, Black, 3m	FL-3C-B-3M		
3 core, Black, Custom Length*	FL-3C-B-ZM		
5 core, Black, 3m	FL-5C-B-3M		
5 core, Black, Custom Length*	FL-5C-B-ZM		
6 core, Black, 3m	FL-6C-B-3M		
6 core, Black, CustomLength*	FL-6C-B-ZM		
White 0.75mm², Supply Cable			
3 core, White, 3m	FL-3C-W-3M		
3 core, White, Custom Length*	FL-3C-W-ZM		
5 core, White, 3m	FL-5C-W-3M		
5 core, White, Custom Length*	FL-5C-W-ZM		
6 core, White, 3m	FL-6C-W-3M		
6 core, White, CustomLength*	FL-6C-W-ZM		
Decorative Ceiling Rose			
Silver RAL9006	CR-75-I-S		
Black RAL9005	CR-75-I-B		
White RAL9016	CR-75-I-W		
Custom RAL Colour**	CR-75-I-Z		
*Please replace Z with required cut meter length.			
**Please replace Z with required Custom RAL Colour.			
TL Snoot			
RAL9005 Black Snoot	Supplied as standard	 	
RAL9016 White Snoot	Available upon request		

RAL9005 Black Snoot

RAL9016 White Snoot



Installation options

Single suspended light

Suspended Cluster feature Light

